

Aquam8620/8120

16+4G Port Layer3/2 Managed EN50155 Industrial Ethernet Switches



» Overview

The Aquam8620/8120 series Layer3/Layer2 EN50155 industrial Ethernet switches, specially designed for rail industries, support up to 16 Fast Ethernet interfaces and 4 Gigabit uplink interfaces, and meet the EN50155, EN50121 and other rail transit industry standards. The switches support IP65 protection class to meet the requirements of dustproof and waterproof performance, and the M12 interface ensures the tightness and the firmness of the port connection, which is especially suitable for applications that are subject to high vibration and shock.

The Aquam8620/8120 series EN50155 industrial Ethernet switches support up to 120W PoE/PoE+ (IEEE 803.2af, IEEE 802.3at). This power can be increased to 240 W by means of an electrically isolated external power supply, which is available separately. Different redundancy protocols and security mechanisms ensure high-availability and secure data communication. A passive bypass function guarantees that networks remain functional even at multiple points of failure. Further features of the switches, which can be put into operation according to the plug-and-play principle, include high shock and vibration resistance, almost complete insensitivity to electromagnetic interference and a temperature range of -40 ° C to + 70 ° C.

Diagnosis is possible via an internal hardware self-test, different IP/MAC conflict alarms and Syslog. Routing functions include Static Routing, Open Shortest Path First (OSPF), and Routing Information Protocol (RIP). Redundancy methods comprise Rapid Spanning Tree Protocol (RSTP), Distributed Redundancy Protocol (DRP), and Media Redundancy Protocol (MRP). The security mechanisms enable for example access control according to IEEE 802.1x, Secure Shell (SSH), and authentication via Radius servers. The Aquam8620/8120 EN50155 industrial Ethernet switches can be widely used in PIS, CCTV, video monitoring system and train control system. They also apply to any other industrial applications of harsh vibration and shock, and high EMC compatibility.

» Key Features

Supports a maximum of 4 10/100/1000Base-TX with X-coded M12 connectors and 16 10/100Base-TX ports with D-coded M12 connectors.

Supports up to 120W PoE/PoE+ (IEEE 802.3af/at) on all 16 10/100Base-TX PoE ports with devices' own 24VDC/110VDC power supplies, and a maximum of 240W PoE/PoE+ with an external 50-54VDC power supply.

Supports optional bypass function

Supports RSTP,DRP,MRP ring network redundancy protocols and VRRP

Supports Layer 3 routing protocols such as static Routing, OSPF and RIP

Complies with IEC61375 standard, supports TTDP (Train Topology Discovery Protocol)

Complies with the requirements of EN50155 and EN50121 industrial standards

IP65 protection class

» Product Specifications

>Software Functions

-Switching

Supports static VLAN, Private VLAN

Supports port flow control

Supports speed limit, Broadcast, Multicast, Unknown unicast storm control

Static and dynamic MAC addresses and MAC address aging

-Redundancy

Supports VRRP

Supports RSTP (Rapid Spanning Tree Protocol)

Supports DRP with recovery time <20ms

Supports MRP (IEC62439-2)

Supports Link Aggregation (LACP, IEEE802.3ad)

-Routing

Supports Static Routing (L3 Switch only)

Supports OSPF (L3 Switch only)

Supports RIP (L3 Switch only)

-Multicast

Supports IGMP snooping

Supports GMRP

Supports PIM-SM, PIM-DM

Supports IGMP v2/v3

-Network Security

Supports IEEE 802.1x(authentication and authorization)

Supports HTTPs/SSL

Supports SSH

Supports a local RADIUS server and also the forwarding of an authentication to an external RADIUS server.

Supports TACACS+

Unicast MAC Filtering

-Service Quality

Supports ACL

Control and limit the data traffic for each port (as well dependent of the protocol)

Supports 802.1p TOS/DiffServ, Supports SP, WRR queue scheduling

-Management and Maintenance

Supports Console, Telnet, WEB management methods

Supports SNMP Management, SNMPv1/v2c/v3

SNMPv3 supports DES and AES encryption

Supports TCP/UDP, Ping, Trace route

Supports upload/download for software and configuration by FTP/TFTP/SFTP/HTTP/HTTPs

Supports port mirroring and remote mirror port

Supports LLDP and LLDP MIB (802.1ab)

Supports the configuration of a maximum packet size (MTU)

Supports ICMP, ICMP Router Discovery

-Diagnosis

Supports internal hardware self-test,

Supports IP/MAC conflict alarm, power failure alarm, port alarm and ring alarm

Supports Syslog, the maximum size of the log file needs to be specified

-IP Management

Supports IPv4

Supports DHCP server/option12

Supports Port Security over DHCP

Supports DHCP-relay-agent/option 82

Supports BOOTP/Bootstrap Protocol

DHCP Relay Agent Information Option

DHCP Client

Supports DNS (L3 Switch only)

Supports ARP

Supports NAT, NAT (L3 Switch only)

-Clock management

Supports SNTP client

Supports NTP client

-Characteristic function

Supports bypass power failure bypass function

Supports IEC 61375 (ETB) (L3 Switch only)

Support TTDP, R-NAT (L3 Switch only)

Supports Auto-Backup and Configuration

-MIB

Public MIB: MIB-II, LLDP MIB, ifXTable, dot1dBridge, TTDP MIB, RSTP MIB, IGMP snooping MIB, MRP MIB, DRP MIB

Private MIB: kylandPort, kylandDev, KylandAlarm, Private LLD, kylandUpdate, kylandUpdateCfg, kylandDownloadCfg

>Technical Specification

-Technical Parameter

Standard

IEEE 802.3 10BASE-T specification

IEEE 802.3x 10BASE-T full duplex

IEEE 802.3u 100BASE-TX specification

IEEE 802.3ab 1000BASE-T specification

IEEE 802.3af

IEEE802.3at

-Switch Properties

Priority Queues 8

Number of VLANs 4K

VLAN ID 1~4094

Number of Multicast Groups IPv4 : 2K

Routing Table IPv4 : 4K

MAC Table 32K

Packet Buffer 32Mb

Packet Forwarding Rate 9.5Mpps

Switching Delay <10us

-Interface

Gigabit Port 10/100/1000Base-T(X) - M12 X-coded connector

Bypass 4 ports of the switch offer two Bypass function

Fast Ethernet Port 10/100Base-T(X) - M12 D-coded connector

PoE Support IEEE803.2af

Support IEEE802.3at

Console Port RS232 - M12 A-coded connector

Alarm contact M12 A-coded connector

USB M12 A-coded connector

-LED

LEDs on Front Panel

Running LED: Run

Alarm LED: Alarm

Power LED: PWR1, PWR2

Interface LED: Link/ACT

POE LED: ACT(POE models only)

-Power Requirements

Power Input

24VDC/110VDC - M23 connector (for switch power supply)

50~54VDC - M12 connector (for additional isolated power supply)

Power Terminal

M23 connector

M12 connector for optional external power supply

Power Consumption

<22W@110VDC without PoE

<160W@110VDC with 120W PoE

PoE output

Integrated power supply provides 80/120W PoE output.

Additional 120W can be increased by adding isolated external power supply.

Overload Protection Support

Reverse Connection Protection Support

Redundancy Protection Support

-Physical Characteristics

Housing Metal

cooling Nature cooling, fanless

Protection Class IP65

Dimensions 189mm×325mm×91.3mm(H×W×D)

Weight 4.25Kg

Mounting Wall mounting

-Environmental Limits

Operating Temperature -40°C to +70°C

Storage Temperature -40°C to +85°C

Ambient Relative Humidity 5 to 95% (non-condensing)

-Warranty

MTBF >300000h (calculation based on Telcordia (Bellcore) SR-332, Issue 2, September 2006)

Warranty Period 5 years

-Approvals

CE, EN50155, EN45545

-Industrial Standard

EMI FCC CFR47 Part 15,EN55022/CISPR22,Class A

EMS DIN EN 50121 / DIN EN 55022

Fire protection DIN EN 45545

Safety EN60950-1


Machinery IEC61373 (Vibration and Shock)

IEC60068-2-32 (Free Fall)

Protection class IP65 Based on EN 60529

Hazardous Matreial 2002/95/EG of the EU (RoHS)

» Mechanical Drawing



» Ordering Information

Ordering Information

Product Model Aquam8X20-B-Ports-PS1-PS2

Code Definition Ordering Codes

X	1 = Layer 2 Switch 6 = Layer 3 Switch
B	4x 100M ports support 2 pairs of Bypass function; 4x 1000M ports support 2 pairs of Bypass function for Models with gigabit ports;
Ports	16T = 16 x 10/100BASE-T(X) M12 port 4GE16T = 4 x 10/100/1000BASE-T(X) M12 port; 16x 10/100BASE-T(X) M12 port 16P = 16 x 10/100BASE-T(X) M12 PoE port 4GE16P = 4 x 10/100BASE-T(X) M12 port; 16x 10/100BASE-T(X) M12 PoE port
PS1-PS2 (Power Supply)	H2-H2=110VDC(77-137.5VDC), redundant power inputs L13-L13=24VDC(16.8-30VDC), redundant power inputs

Accessories

Accessory Model	Description	Note
M23-A-7P-F	Female cable connector with M23, A-Coding, 7 Pin	Power interface Connector
M12-A-4P-M	Male cable connector with M12, A-Coding, 4 Pin	Console or USB interface Connector
M12-A-4P-M	Male cable connector with M12, A-Coding, 4 Pin	Alarm connector
M12-D-4P-M	Male cable connector with M12, D-Coding, 4 Pin	10/100Base-TX interface Connector
M12-X-8P-M	Male cable connector with M12, X-Coding, 8 Pin	10/100/1000Base-TX Connector

Version:2018-02-12 10:00:15